

## CONTACT PRODUCT SHEET

Date: 11/2014

### PRODUCT

Tierrafino Contact serves as a primer/mechanical key for clay- and other Description:

plasters for smooth and/or very absorbing substrates in the interior.

Composition: Tree resin binder, calcium carbonate, titane oxide, water, additives,

preservative.

5 | & 10 | buckets. Packaging:

Consumption: Approx. 0,25 l/m<sup>2</sup> onto smooth substrates. Consumption is greater when

applied onto rough substrates.

Storage advice: Store dry and cool but free of frost.

Workability: Once opened, Contact must be used within 1 year.

### AREA OF APPLICATION

Contact is applied onto smooth walls and ceilings in the interior like prepared dry wall systems, smooth gypsum-, lime-, cement- and other plasters, concrete, smooth bricks and other blocks. Only applicable in the exterior where protected from direct contact with water. Suitable for humid rooms, do not apply where there is a chance of direct contact with water. Contact is developed to be an adhesion primer for Tierrafino Base, Finish,

Kalk and Kalk Fine.

#### PROPERTIES • Ready to use

- Easily applied with brush or roller
- White in color before and after drying
- Odorless after drying
- Contains no VOC's
- Water vapour permeable
- Not suitable for humid substrates

## APPLICATION

The air- and substrate temperature must be at least 5°C. Circumstances:

Substrate: Continuously dry and free of dust and grease. Roughen very smooth, non

absorbing surfaces using sandpaper.

Stir well before use. Dilute with max. 5% water when applied onto very Mixing:

absorbing substrates.

Application: Apply Contact with a brush or a roller. Distribute sand evenly. Use a good

quality masking tape on substrates and on dried out Contact when

applying a plaster.

Under normal circumstances (+20°C and 60% relative air humidity), Drying time:

Contact is dry between 4-12 hours. Hardened out after 2 days.

Thinner: Water. Dilute with max. 5% water.



# CONTACT PRODUCT SHEET

Date: 11/2014

Safety advice:

Avoid contact with eyes and mucous membranes. With induced risk (ceilings) wear safety goggles. For further information consult the Contact Material Safety Data Sheet.

TOOLS

Stirring stick, paint brush, roller, masking tape.



DISCLAIMER

Although this product description has been put together with utmost precision, Tierrafino will not be liable for any indirect or direct damage that may occur, by using the information offered in this product description.